Page 1 of 5

Material Safety Data Sheet

1. Product and Company Identification

Product Name: Paint Sealer Stripper

Trade Name: Paint Sealer Stripper

Revision Date: 05/11/08

Company Name: On-Crete Australia Pty Ltd

Address: 4/66 Casua Dr, Varsity Lakes

QLD 4227 Australia

Ph: (07) 5593 6884 Fax: (07) 5593 6885

In the event of emergency

human exposure: Poisons Information Centre

Ph: 131136

Hazardous according to the criteria of NOHSC

2. Composition/Information on Ingredients

Ingredients considered hazardous according to the criteria of Worksafe Australia:

Chemical NameCAS #ProportionEU ClassificationMethylene Chloride[75-09-2]30-60%Xn; R40, R20/R22

Formic Acid [64-18-6] 10-<30% C; R34

Ingredients determined not to be hazardous to 100%

Notes on EU Symbols: Xn Harmful, C Corrosive

3. Hazards Identification

Harmful: Possible Risks of Irreversible Effects

Corrosive: Causes Burns
Harmful: By Inhalation
Harmful: If Swallowed

4. First Aid Measures

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids apart to ensure flushing of the entire eye surface. IMMEDIATE medical attention is necessary

Ingestion:

Give patient as much water as possible short of vomiting. IMMEDIATE medical attention is necessary. Tell doctor that liver and kidney failure may occur.

Inhalation:

Page 2 of 5

Remove victim to fresh air. Persons administering first aid to overexposure victims should carefully wash off any visible product from the victims face. Do not give anything by mouth to an unconscious person. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult administer oxygen. Get medical attention IMMEDIATELY.

Skin:

Wash with plenty of soap and water. Remove contaminated clothing and footwear. Wash clothing and contaminated footwear before reuse. Seek medical attention.

5. Fire-Fighting Measures

Flash Point: N/A

Extinguisher Media: Foam, carbon dioxide, dry chemical.

Unusual Fire and Explosion Hazards: None known

Special Protective Equipment: Fires in confined spaces should be dealt with by

trained personnel wearing approved breathing

apparatus.

6. Accidental Release Measures

Steps to be taken if material is released or spilled:

Wear appropriate protective clothing. Eliminate all ignition sources. Restrict access to contaminated area. Stop spill at source. Dike to prevent spreading. Collect free liquid into a recovery vessel. Absorb remainder with sand or clay and place in a properly labelled waste receptacle. Follow all government and local body regulations for disposal. Do not contaminate water while cleaning equipment or disposing of wastes. Prohibit contamination of streams, lakes and other bodies of water.

Container Disposal:

DO NOT reuse container. Dispose of safely.

7. Handling and Storage

Handling:

Avoid contact with eyes and skin
Do not breathe vapour
Wear gloves and suitable protective clothing

Storage:

Store in a cool, dry place locked out of reach of children in lacquer, plastic or poly-lined containers. A pressure build up may occur. If this happens release the bung slowly until hissing has stopped.

8. Exposure Controls/Personal Protection

Ventilation Requirements:

Ventilate via mechanical methods (general or local exhaust) to maintain exposure below 5mg/m3. Good industrial hygiene practise dictates that indoor work areas should be isolated and provided with adequate local exhaust ventilation.

Respiratory Protection:

Filtered masks must be worn

Eye Protection:

Page 3 of 5

Safety glasses with a side shield or full-face shield must be worn

Skin Protection:

PVC Gauntlet gloves must be worn, along with a plastic apron

Other precautions:

This product may produce severe skin burns and is harmful by ingestion and inhalation. DO NOT SMOKE when using this product

9. Physical and Chemical Properties

Appearance: Semi transparent gel

Odour: Significant solvent odour.

Boiling Point 40 degrees Celsius

Specific Gravity: 1.24 @ 20 degrees Celsius

Solubility in Water: Partially soluble

Flash Point: N/A

10. Stability and Reactivity

Stability: High temperature may contribute to instability

Incompatibility: Will attack many plastics and bitumen but is

otherwise stable. Corrosive to most metals

Hazardous Decomposition Products: Chloride and Phosgene fumes.

Hazardous Polymerisation: Will not occur

9. Toxicological Data

Acute over exposure to this product could be fatal and may see the development of shock, followed by unconsciousness, accompanied by liver and kidney failure as late complications. LD50 Oral Rat: >1610 mg/kg (estimate based on raw material data)

Eyes:

Severe pain and corneal burns will occur, and possible irreversible damage

Ingestion:

Nausea, vomiting and sweating with burns to the mouth, oesophagus and stomach may occur. Unconsciousness may follow. Ingestion is harmful and may be fatal.

Inhalation:

Dizziness and shortness of breath occur from mild poisoning. In severe cases, congestion, shock, unconsciousness and convulsions may occur.

Skin:

Severe burns may result from contact with skin. These are painless and show up as white and later red blotches. Blistering and loss of skin may result. This product is absorbed through the skin.

Page 4 of 5

12. Ecological Information

Hazard:

When using this product outside, use containment procedures to avoid unnecessary contact with the environment

This product is toxic to marine organisms.

13. Disposal Considerations

Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

Incineration may be carried out under controlled conditions provided that local regulations for emissions are met.

Dispose of product and container responsibly and carefully.

Do not dispose of near waterways, down drains or into soil.

14. Transport Information

Classified as hazardous for transport (ADG, UN, IATA/ICAO)

Dangerous Goods Class: 6.1 Subsidiary Risk 8 Toxic Liquid, Corrosive, Organic, NOS

15. Regulatory Information

Australian Classifications:

UN Number: 2927 HAZCHEM Code: 2XZ Poison Schedule: 6

Dangerous Goods Class 6.1 Subsidiary Risk 8 Toxic Liquid, Corrosive, Organic, NOS

Packaging Group:

EC Labelling: Harmful: Possible Risks of Irreversible Effects

Corrosive: Causes Burns Harmful: By Inhalation Harmful: If Swallowed

S (1, 2); Keep locked up and out of reach of children

S 24, 25 Avoid contact with eyes and skin

S 23 Do not breathe vapour

S 36, 37 Wear gloves and suitable protective clothing

S 26 In case of contact with eyes, rinse

immediately with plenty of water and seek

medical advice

S 45 In case of accident or if you feel unwell seek

medical advice immediately and show this

container or label.

16. Other Information

This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified. However no warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and the information in this data sheet.

Page 5 of 5

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Oncrete shall not be responsible for any damage of injury resulting from abnormal use of this material, from any failure to adhere to recommendations or from any hazards inherent in the nature of the material.